


RECTANGULAR HOLLOW SECTIONS EN 10219 - 1 & 2 : 2006


Size H x B mm	Thickness T mm	Mass M kg/m	Size H x B mm	Thickness T mm	Mass M kg/m
40 x 20	1.2	1.06		5.0	6.85
	1.5	1.30		6.0	7.99
	1.8	1.53		6.3	8.31
	2.0	1.68	65 x 35	2.0	2.93
	2.5	2.03		2.5	3.60
	3.0	2.36		3.0	4.25
50 x 25	1.5	1.65	75 x 50	1.5	2.83
	1.8	1.95		1.8	3.37
	2.0	2.15		2.0	3.72
	2.5	3.07		2.5	4.58
	3.0	3.88		3.0	5.42
	4.0			4.0	7.02
50 x 30	2.5	2.89		5.0	8.52
	3.0	3.41		6.0	9.92
	3.2	3.61	80 x 40	3.0	5.29
	4.0	4.39		3.2	5.62
	4.9	5.20		4.0	6.90
	5.0	5.28		4.9	8.28
60 x 30	1.5	2.00		5.0	8.42
	1.8	2.38		6.0	9.87
	2.0	2.62		6.3	10.3
	2.5	3.21		8.0	12.5
	3.0	3.77			
	4.0	4.83			
60 x 40	2.5	3.68			
	3.0	4.35			
	3.2	4.62			
	4.0	5.64			
	4.9	6.74			



RECTANGULAR HOLLOW SECTIONS EN 10219 - 1 & 2 : 2006

Size H x B mm	Thickness T mm	Mass M kg/m
90 x 50	3.0	6.24
	3.2	6.63
	3.6	7.40
	4.0	8.15
	4.9	9.81
	5.0	9.99
	5.6	11.1
	6.0	11.8
	6.3	12.3
	7.1	13.6
	8.0	15.0
100x50	3.2	7.13
	3.6	7.96
	4.0	8.78
	4.9	10.6
	5.0	10.8
	6.0	12.7
	6.3	13.3
	7.1	14.7
	8.0	16.3
100x60	3.0	7.18
	3.2	7.63
	3.6	8.53
	4.0	9.41
	4.9	11.4
	5.0	11.6
	5.6	12.8
	6.0	13.6
	6.3	14.2
	7.1	15.8


Size H x B mm	Thickness T mm	Mass M kg/m
120x 60	8.0	17.5
	3.6	9.7
	4.0	10.7
	4.9	12.9
	5.0	13.1
	5.6	14.6
	6.0	15.5
	6.3	16.2
120x 80	7.1	18.1
	8.0	20.1
	3.6	10.8
	4.0	11.9
	4.9	14.4
	5.0	14.7
	5.6	16.3
	6.0	17.4
	6.3	18.2
	7.1	20.3
125 x 75	8.0	22.6
	10.0	27.4
	2.5	7.53
	3.0	8.96
	4.0	11.70
	4.5	13.08
	5.0	14.40
	5.5	15.71
	6.0	17.00



RECTANGULAR HOLLOW SECTIONS


EN 10219 - 1 & 2 : 2006

Size H x B mm	Thickness T mm	Mass M kg/m	Size H x B mm	Thickness T mm	Mass M kg/m
150 x 75	2.0	6.86	180x 100	12.0	39.5
	2.5	8.51		12.5	40.9
	3.0	10.13		5.0	21.0
	4.0	13.30		5.6	23.4
	4.5	14.85		6.0	24.9
	5.0	16.37		6.3	26.1
	5.5	17.87		7.1	29.2
	6.0	19.09		8.0	32.6
150x 100	8.0	21.53		8.8	35.6
	4.0	15.1		10.0	40.0
	4.9	18.3		12.0	47.0
	5.0	18.6		12.5	48.7
	5.6	20.7	200x 100	5.0	22.6
	6.0	22.1		5.6	25.1
	6.3	23.1		6.0	26.8
	7.1	25.9		6.3	28.1
	8.0	28.9		7.1	31.4
	8.8	31.5		8.0	35.1
	10.0	35.3		8.8	38.4
	12.0	41.4		10.0	43.1
	12.5	42.8		12.0	50.8
160 x 80	4.0	14.4		12.5	52.7
	4.9	17.5		14.2	58.9
	5.0	17.8		16.0	65.2
	5.6	19.9	200x 120	5.0	24.1
	6.0	21.2		5.6	26.9
	6.3	22.2		6.0	28.7
	7.1	24.7		6.3	30.1
	8.0	27.6		7.1	33.7
	8.8	30.1		8.0	37.6
	10.0	33.7			



RECTANGULAR HOLLOW SECTIONS EN 10219 - 1 & 2 : 2006


Size H x B mm	Thickness T mm	Mass M kg/m	Size H x B mm	Thickness T mm	Mass M kg/m
	8.8	41.1	250x 150	5.0	30.4
	10.0	46.3		5.6	33.9
	12.0	54.6		6.0	36.2
	12.5	56.6		6.3	38.0
	14.2	63.3		7.1	42.6
	16.0	70.2		8.0	47.7
				8.8	52.2
200x 150	5.0	26.5		10.0	58.8
	5.6	29.5		12.0	69.6
	6.0	31.5		12.5	72.3
	6.3	33.0		14.2	81.1
	7.1	37.0		16.0	90.3
	8.0	41.4	260x 140	5.0	30.4
	8.8	45.3		5.6	33.9
	10.0	51.0		6.0	36.2
	12.0	60.2		6.3	38.0
	12.5	62.5		7.1	42.6
	14.2	70.0		8.0	47.7
	16.0	77.7		8.8	52.2
250x 100	5.0	26.5		10.0	58.8
	5.6	29.5		12.0	69.6
	6.0	31.5		12.5	72.3
	6.3	33.0		14.2	81.1
	7.1	37.0		16.0	90.3
	8.0	41.4	300x 100	5.0	30.4
	8.8	45.3		5.6	33.9
	10.0	51.0		6.0	36.2
	12.0	60.2		6.3	38.0
	12.5	62.5		7.1	42.6
	14.2	70.0		8.0	47.7
	16.0	77.7			



RECTANGULAR HOLLOW SECTIONS

EN 10219 - 1 & 2 : 2006


Size H x B mm	Thickness T mm	Mass M kg/m	Size H x B mm	Thickness T mm	Mass M kg/m
300x 200	5.0	38.3	400x 300	8.0	85.4
	5.6	42.7		8.8	93.6
	6.0	45.7		10.0	106
	6.3	47.9		12.0	126
	7.1	53.7		12.5	131
	8.0	60.3		14.2	148
	8.8	66.0		16.0	166
	10.0	74.5	500x 300	8.0	97.0
	12.0	88.5		12.0	145.6
	12.5	91.9		16.0	194.7
	14.2	103			
	16.0	115			
400x 200	6.0	55.1			
	6.3	57.8			
	7.1	64.9			
	8.0	72.8			
	8.8	79.8			
	10.0	90.2			
	12.0	107			
	16.0	141			
450x 250	8.0	85.4			
	10.0	106			
	12.0	126			
	16.0	166			



SQUARE HOLLOW SECTIONS

EN 10219 - 1 & 2 : 2006


			Size H x B mm	Thickness T mm	Mass M kg/m
25 x 25	1.2	0.87		5.0	8.42
	1.5	1.06		6.0	9.87
	1.8	1.25		6.3	10.3
	2.0	1.36		8.0	12.5
	2.3	1.53			
	2.5	1.64			
	3.0	1.89			
30 x 30	1.2	1.06	65 x 65	2.0	3.94
	1.5	1.30		2.5	29.57
	1.8	1.53		3.0	35.49
	2.0	1.68			
	2.5	2.03			
	3.0	2.36			
	4.0	2.94			
40 x 40	2.5	2.89	70 x 70	3.0	6.24
	3.0	3.41		3.2	6.63
	3.2	3.61		3.6	7.40
	4.0	4.39		4.0	8.15
	4.9	5.20		4.9	9.81
	5.0	5.28		5.0	9.99
				6.0	11.8
50 x 50			75 x 75	6.3	12.3
				7.1	13.6
				8.0	15.0
	2.5	3.68			
	3.0	4.35		2.5	5.56
	3.2	4.62		3.0	6.60
	4.0	5.64		4.0	8.59
60 x 60	4.9	6.74	80 x 80	5.0	10.50
	5.0	6.85		6.0	12.30
	6.0	7.99			
	6.3	8.31		3.2	7.63
				3.6	8.53
				4.0	9.41
				4.9	11.4
	3.0	5.29		5.0	11.6
	3.2	5.62		5.6	12.8
	4.0	6.90		6.0	13.6
	4.9	8.28			



SQUARE HOLLOW SECTIONS EN 10219 - 1 & 2 : 2006

Size H x B mm	Thickness T mm	Mass M kg/m
90 x 90	6.3	14.2
	7.1	15.8
	3.6	9.66
	4.0	10.7
	4.9	12.9
	5.0	13.1
	5.6	14.6
	6.0	15.5
	6.3	16.2
100 x 100	7.1	18.1
	8.0	20.1
	3.6	10.8
	4.0	11.9
	4.9	14.4
	5.0	14.7
	5.6	16.3
	6.0	17.4
	6.3	18.2
120 x 120	7.1	20.3
	8.0	22.6
	10.0	27.4
	4.0	14.4
	4.9	17.5
	5.0	17.8
	5.6	19.9
	6.0	21.2
	6.3	22.2
	7.1	24.7
	8.0	27.6
	8.8	30.1
	10.0	33.7

Size H x B mm	Thickness T mm	Mass M kg/m
125 x 125	12.0	39.5
	12.5	40.9
	2.5	9.49
	3.0	11.31
	4.0	14.90
	5.0	18.30
	6.0	21.70
	8.0	27.70
	9.0	30.60
140 x 140	4.9	20.6
	5.0	21.0
	5.6	23.4
	6.0	24.9
	6.3	26.1
	7.1	29.2
	8.0	32.6
	8.8	35.6
	10.0	40.0
150 x 150	12.0	47.0
	12.5	48.7
	4.9	22.1
	5.0	22.6
	5.6	25.1
	6.0	26.8
	6.3	28.1
	7.1	31.4
	8.0	35.1
	8.8	38.4
	10.0	43.1
	12.0	50.8



SQUARE HOLLOW SECTIONS

EN 10219 - 1 & 2 : 2006

Size H x B mm	Thickness T mm	Mass M kg/m
160x 160	12.5	52.7
	16.0	65.2
	5.0	24.1
	5.6	26.9
	6.0	28.7
	6.3	30.1
	7.1	33.7
	8.0	37.6
	8.8	41.1
	10.0	46.3
180x 180	12.0	54.6
	12.5	56.6
	14.2	63.3
	16.0	70.2
	5.0	27.3
	5.6	30.4
	6.0	32.5
	6.3	34.0
200x 200	7.1	38.1
	8.0	42.7
	8.8	46.7
	10.0	52.5
	12.0	62.1
	12.5	64.4
	14.2	72.2
	16.0	80.2

Size H x B mm	Thickness T mm	Mass M kg/m
200x 200	6.3	38.0
	7.1	42.6
	8.0	47.7
	8.8	52.2
	10.0	58.8
	12.0	69.6
	12.5	72.3
	14.2	81.1
250x 250	16.0	90.3
	5.0	38.3
	5.6	42.7
	6.0	45.7
	6.3	47.9
	12.5	91.9
	12.0	88.5
	14.2	103
300 x 300	16.0	115
	6.0	54.7
	8.0	72.8
	10.0	88.4
	12.0	109.2
350 x 350	16.0	144.0
	8.0	84.93
	10.0	106.0
400 x 400	12.0	127.4
	8.0	97.0
	10.0	121.3
	12.0	145.6
	16.0	194.7

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Nominal Size Inches	Outside diameter		Wall thickness		Weight		Identification				
							API Specifications			W. T. Std - XS XXS	N° Schedule
	Inches	mm	Inches	mm	lbs/foot	kg/m	5L 3182	5LX 3/82	5LS 3/82		
1/8	0.405	10.3	0.068	1.73	0.24	0.37	x			STD	40
	0.405	10.3	0.095	2.41	0.31	0.47	x			XS	80
1/4	0.540	13.7	0.088	2.24	0.42	0.63	x			STD	40
	0.540	13.7	0.119	3.02	0.54	0.80	x			XS	80
3/8	0.675	17.1	0.091	2.31	0.57	0.84	x			STD	40
	0.675	17.1	0.126	3.20	0.74	1.10	x			XS	80
1/2	0.840	21.3	0.109	2.77	0.85	1.27	x			STD	40
	0.840	21.3	0.147	3.73	1.09	1.62	x			XS	80
	0.840	21.3	0.188	4.78	1.31	1.95					160
	0.840	21.3	0.294	7.47	1.71	2.55	x			XXS	
3/4	1.050	26.7	0.113	2.87	1.13	1.69	x			STD	40
	1.050	26.7	0.154	3.91	1.47	2.20	x			XS	80
	1.050	26.7	0.219	5.56	1.94	2.90					160
	1.050	26.7	0.308	7.82	2.44	3.64	x			XXS	
1	1.315	33.4	0.133	3.38	1.68	2.50	x			STD	40
	1.315	33.4	0.179	4.55	2.17	3.24	x			XS	80
	1.315	33.4	0.250	6.35	2.84	4.24					160
	1.315	33.4	0.358	9.09	3.66	5.45	x			XXS	
1 1/4	1.660	42.2	0.140	3.56	2.27	3.39	x			STD	40
	1.660	42.2	0.191	4.85	3.00	4.47	x			XS	80
	1.660	42.2	0.250	6.35	3.76	5.61					160
	1.660	42.2	0.382	9.70	5.21	7.77	x			XXS	
1 1/2	1.900	48.3	0.145	3.68	2.72	4.05	x			STD	40
	1.900	48.3	0.200	5.08	3.63	5.41	x			XS	80
	1.900	48.3	0.281	7.14	4.86	7.25					160
	1.900	48.3	0.400	10.15	6.41	9.56	x			XXS	

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Nominal Size Inches	Outside diameter		Wall thickness		Weight		Identification				
	Inches	mm	Inches	mm	lbs/foot	kg/m	API Specifications			w. T. Std - XS XXS	N° Schedule
							5LX 3/82	5LX 3/82	5LS 3/82		
2	2.375	60.3	0.083	2.11	2.03	3.03	x	x			
	2.375	60.3	0.109	2.77	2.64	3.93	x	x			
	2.375	60.3	0.125	3.18	3.00	4.48	x	x			
	2.375	60.3	0.141	3.58	3.36	5.01	x	x			
	2.375	60.3	0.154	3.91	3.65	5.44	x	x		STD	40
	2.375	60.3	0.172	4.37	4.05	6.03	x	x			
	2.375	60.3	0.188	4.78	4.39	6.54	x	x			
	2.375	60.3	0.218	5.54	5.02	7.48	x	x		XS	80
	2.375	60.3	0.250	6.35	6.67	8.45	x	x			
	2.375	60.3	0.281	7.14	6.28	9.36	x	x			
	2.375	60.3	0.344	8.74	7.46	11.11					160
	2.375	60.3	0.436	11.07	9.03	13.44	x	x		XXS	
2 1/2	2.875	73.0	0.083	2.11	2.47	3.69	x	x			
	2.875	73.0	0.109	2.77	3.22	4.80	x	x			
	2.875	73.0	0.125	3.18	3.67	5.48	x	x			
	2.875	73.0	0.141	3.58	4.12	6.13	x	x			
	2.875	73.0	0.156	3.96	4.53	6.74	x	x			
	2.875	73.0	0.172	4.37	4.97	7.40	x	x			
	2.875	73.0	0.188	4.78	5.40	8.04	x	x			
	2.875	73.0	0.203	5.16	5.79	8.63	x	x		STD	40
	2.875	73.0	0.216	5.49	6.13	9.14	x	x			
	2.875	73.0	0.250	6.35	7.01	10.44	x	x			
	2.875	73.0	0.276	7.01	7.66	11.41	x	x		XS	80
	2.875	73.0	0.375	9.53	10.01	14.92					160
	2.875	73.0	0.552	14.02	13.69	20.39	x	x		XXS	
3	3.500	88.9	0.083	2.11	3.03	4.52	x	x			
	3.500	88.9	0.109	2.77	3.95	5.88	x	x			
	3.500	88.9	0.125	3.18	4.51	6.72	x	x			
	3.500	88.9	0.141	3.58	5.06	7.53	x	x			
	3.500	88.9	0.156	3.96	5.57	8.29	x	x			

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Nominal Size Inches	Outside diameter		Wall thickness		Weight		Identification				
	Inches	mm	Inches	mm	lbs/foot	kg/m	API Specifications			w. T. Std - XS XXS	Nº Schedule
							5Lx 3/82	5LX 3/82	5LS 3/82		
3	3.500	88.9	0.172	4.37	6.11	9.11	x	x			
	3.500	88.9	0.188	4.78	6.65	9.92	x	x			
	3.500	88.9	0.216	5.49	7.58	11.29	x	x		STD	40
	3.500	88.9	0.250	6.35	8.68	12.93	x	x			
	3.500	88.9	0.281	7.14	9.66	14.40	x	x			
	3.500	88.9	0.300	7.62	10.25	15.27	x	x		XS	80
	3.500	88.9	0.438	11.13	14.32	21.35					160
	3.500	88.9	0.600	15.24	18.58	27.68	x	x		XXS	
3 1/2	4.000	101.6	0.083	2.11	3.47	5.18	x	x			
	4.000	101.6	0.109	2.77	4.53	6.75	x	x			
	4.000	101.6	0.125	3.18	5.17	7.72	x	x			
	4.000	101.6	0.141	3.58	5.81	8.65	x	x			
	4.000	101.6	0.156	3.96	6.40	9.53	x	x			
	4.000	101.6	0.172	4.37	7.03	10.48	x	x			
	4.000	101.6	0.188	4.78	7.65	11.41	x	x			
	4.000	101.6	0.226	5.74	9.11	13.57	x	x		STD	40
	4.000	101.6	0.250	6.35	10.01	14.92	x	x			
	4.000	101.6	0.281	7.14	11.16	16.63	x	x			
	4.000	101.6	0.318	8.08	12.50	18.63	x	x		XS	80
4	4.500	114.3	0.083	2.11	3.92	5.84	x	x	x		
	4.500	114.3	0.109	2.77	5.11	7.62	x		x		
	4.500	114.3	0.125	3.18	5.84	8.71	x	x	x		
	4.500	114.3	0.141	3.58	6.56	9.77	x	x	x		
	4.500	114.3	0.156	3.96	7.24	10.78	x	x	x		
	4.500	114.3	0.172	4.37	7.95	11.85	x	x	x		
	4.500	114.3	0.188	4.78	8.66	12.91	x	x	x		
	4.500	114.3	0.203	5.16	9.32	13.89	x	x	x		
	4.500	114.3	0.219	5.56	10.01	14.91	x	x	x		
	4.500	114.3	0.237	6.02	10.79	16.07	x	x	x	STD	40
	4.500	114.3	0.250	6.35	11.35	16.90	x	x	x		
	4.500	114.3	0.281	7.14	12.66	18.87	x	x	x		
	4.500	114.3	0.312	7.92	13.96	20.78	x	x	x		
	4.500	114.3	0.337	8.56	14.98	22.32	x	x	x	XS	80
	4.500	114.3	0.438	11.13	19.00	28.32	x	x	x		120
	4.500	114.3	0.531	13.49	22.51	33.54	x	x	x		160
	4.500	114.3	0.674	17.12	27.54	41.03	x	x	x	XXS	
5	5.563	141.3	0.083	2.11	4.86	7.24	x		x		
	5.563	141.3	0.125	3.18	7.26	10.83	x		x		

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Nominal Size Inches	Outside diameter		Wall thickness		Weight		Identification				
							API Specifications			w. T. Std - XS XXS	Nº Schedule
	Inches	mm	Inches	mm	lbs/foot	kg/m	5Lx 3/82	5LX 3/82	5LS 3/82		
5	5.563	141.3	0.156	3.96	9.01	13.41	x	x	x	STD	40
	5.563	141.3	0.188	4.78	10.79	16.09	x		x		
	5.563	141.3	0.219	5.56	12.50	18.61	x		x		
	5.563	141.3	0.258	6.55	14.62	21.77	x		x		
	5.563	141.3	0.281	7.14	15.85	23.62	x		x		
	5.563	141.3	0.312	7.92	17.50	26.05	x		x	XS	80 120 160
	5.563	141.3	0.344	8.74	19.17	28.57	x		x		
	5.563	141.3	0.375	9.53	20.78	30.97	x				
	5.563	141.3	0.500	12.70	27.04	40.28	x		x		
	5.563	141.3	0.625	15.88	32.96	49.11	x		x		
	5.563	141.3	0.750	19.05	38.55	57.43	x			XXS	
6	6.625	168.3	0.083	2.11	5.80	8.65	x	x	x	STD	40
	6.625	168.3	0.109	2.77	7.59	11.31	x	x	x		
	6.625	168.3	0.125	3.18	8.68	12.95	x	x	x		
	6.625	168.3	0.141	3.58	9.76	14.54	x	x	x		
	6.625	168.3	0.156	3.96	10.78	16.05	x	x	x		
	6.625	168.3	0.172	4.37	11.88	17.67	x	x	x		
	6.625	168.3	0.188	4.78	12.92	19.27	x	x	x		
	6.625	168.3	0.203	5.16	13.92	20.76	x	x	x		
	6.625	168.3	0.219	5.56	14.98	22.31	x	x	x		
	6.625	168.3	0.250	6.35	17.02	25.36	x	x	x		
	6.625	168.3	0.280	7.11	18.97	28.26	x	x	x	XS	80 120 160
	6.625	168.3	0.312	7.92	21.04	31.32	x	x	x		
	6.625	168.3	0.344	8.74	23.08	34.39	x	x	x		
	6.625	168.3	0.375	9.53	25.03	37.31	x	x	x		
	6.625	168.3	0.432	10.97	28.57	42.56	x	x	x		
	6.625	168.3	0.500	12.70	32.71	48.73	x	x	x	XXS	
	6.625	168.3	0.562	14.27	36.39	54.20	x	x	x		
	6.625	168.3	0.625	15.88	40.05	59.69	x	x	x		
	6.625	168.3	0.719	18.26	45.35	67.56	x	x	x		
	6.625	168.3	0.864	21.95	53.16	79.22	x				
8	8.625	219.1	0.125	3.18	11.35	16.93	x	x	x		
	8.625	219.1	0.156	3.96	14.11	21.01	x	x	x		
	8.625	219.1	0.188	4.78	16.94	25.26	x	x	x		
	8.625	219.1	0.203	5.16	18.26	27.22		x	x		

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Nominal Size Inches	Outside diameter		Wall thickness		Weight		Identification				
							API Specifications			w. T. Std - XS XXS	Nº Schedule
	Inches	mm	Inches	mm	lbs/foot	kg/m	5Lx 3/82	5Lx 3/82	5Lx 3/82		
8	8.625	219.1	0.219	5.56	19.66	29.28	x	x	x	STD	20 30
	8.625	219.1	0.250	6.35	22.36	33.31	x	x	x		
	8.625	219.1	0.277	7.04	24.70	36.81	x	x	x		
	8.625	219.1	0.312	7.92	27.70	41.24	x	x	x		40
	8.625	219.1	0.322	8.18	28.55	42.55	x	x	x		
	8.625	219.1	0.344	8.74	30.42	45.34	x	x	x	XS	60
	8.625	219.1	0.375	9.53	33.04	49.25	x	x	x		
	8.625	219.1	0.406	10.31	35.64	53.08	x	x	x		80
	8.625	219.1	0.438	11.13	38.30	57.08	x	x	x		
	8.625	219.1	0.500	12.70	43.39	64.64	x	x	x	XXS	100
	8.625	219.1	0.562	14.27	48.40	72.08	x	x	x		
	8.625	219.1	0.594	15.09	50.95	75.92	x	x	x		120
	8.625	219.1	0.625	15.88	53.40	79.58	x	x	x		
	8.625	219.1	0.719	18.26	60.71	90.44	x	x	x		140
	8.625	219.1	0.812	20.62	67.76	100.92	x	x	x		
	8.625	219.1	0.875	22.23	72.42	107.92	x	x	x		160
	8.625	219.1	0.906	23.01	74.69	111.27	x	x	x		
10	10.750	273.1	0.156	3.96	17.65	26.28	x	x	x	STD	20
	10.750	273.1	0.188	4.78	21.21	31.63	x	x	x		
	10.750	273.1	0.203	5.16	22.87	34.09	x	x	x		
	10.750	273.1	0.219	5.56	24.63	36.68	x	x	x	XS	30
	10.750	273.1	0.250	6.35	28.04	41.77	x	x	x		
	10.750	273.1	0.279	7.09	31.20	46.51	x	x	x		40
	10.750	273.1	0.307	7.80	34.24	51.03	x	x	x		
	10.750	273.1	0.344	8.74	38.23	56.98	x	x	x	XXS	60
	10.750	273.1	0.365	9.27	40.48	60.31	x	x	x		
	10.750	273.1	0.438	11.13	48.24	71.90	x	x	x		80
	10.750	273.1	0.500	12.70	54.74	81.55	x	x	x		
	10.750	273.1	0.562	14.27	61.15	91.08	x	x	x	XXS	100
	10.750	273.1	0.594	15.09	64.43	96.01	x	x	x		
	10.750	273.1	0.625	15.88	67.58	100.73	x	x	x		120
	10.750	273.1	0.719	18.26	77.03	114.75	x	x	x		
	10.750	273.1	0.812	20.62	86.18	128.38	x	x	x		140
	10.750	273.1	0.844	21.44	89.29	133.06	x	x	x		
	10.750	273.1	1.000	25.40	104.13	155.15	x	x	x	160	160
	10.750	273.1	1.125	28.58	115.64	172.33	x	x	x		

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Nominal Size Inches	Outside diameter		Wall thickness		Weight		Identification					
	Inches	mm	Inches	mm	lb/foot	kg/m	API Specifications			W. T. SW - XS XXS	N° Schedule	
							5Lx 3/82	5LX 3/82	5Ls 3/82			
12	12.750	323.9	0.172	4.37	23.11	34.43	x	x	x	STD	20	
	12.750	323.9	0.188	4.78	25.22	37.62	x	x	x			
	12.750	323.9	0.203	5.16	27.20	40.56		x	x			
	12.750	323.9	0.219	5.56	29.31	43.65	x	x	x			
	12.750	323.9	0.250	6.35	33.38	49.73	x	x	x			
	12.750	323.9	0.281	7.14	37.42	55.77	x	x	x		30	
	12.750	323.9	0.312	7.92	41.45	61.71	x	x	x			
	12.750	323.9	0.330	8.38	43.77	65.20	x	x	x			
	12,750	323.9	0.344	8.74	45.58	67.93	x	x	x			
	12.750	323.9	0.375	9.53	49.56	73.88	x	x	x			40
	12.750	323.9	0.406	10.31	53.52	79.73	x	x	x			
	12.750	323,9	0.438	11.13	57.59	85.84	x	x	x			
	12.750	323.9	0.500	12.70	65.42	97.46	x	x	x	XS		
	12.750	323.9	0.562	14.27	73.15	108.96	x	x	x			
	12.750	323.9	0.625	15.88	80.93	120.62	x	x	x		60	
	12.750	323.9	0.688	17.48	88.63	132.08	x	x	x			
	12.750	323.9	0.750	19.05	96.12	143.21	x	x	x			80
	12,750	323.9	0.812	20.62	103.53	154.21	x	x	x			
	12.750	323.9	0.844	21.44	107.32	159.91				100		
	12.750	323.9	0.875	22.23	110.97	165.37	x	x	x			
12.750	323.9	1.000	25,40	125.49	186.97				XXS			
12.750	323.9	1.125	28.58	139.67	208.14							
12.750	323.9	1.312	33.32	160.27	238.76							
14	14.000	355.6	0.188	4.78	27.73	41.35	x	x		x	STD	10
	14.000	355.6	0.203	5.16	29.91	44.59	x	x		x		
	14.000	355.6	0.210	5.33	30.93	46.04	x	x	x			
	14.000	355.6	0.219	5,56	32.23	47.99	x	x	x			
	14.000	355.6	0.250	6.35	36.71	54.69	x	x	x	20		
	14.000	355.6	0.281	7.14	41.17	61.35	x	x	x			
	14.000	355.6	0.312	7.92	45.61	67.90	x	x	x			
	14.000	355.6	0.344	8.74	50,17	74.76	x	x	x			
	14.000	355.6	0.375	9,53	54.57	81.33	x	x	x	30		
	14.000	355.6	0.406	10.31	58.94	87.79	x	x	x			
	14.000	355.6	0.438	11.13	63.44	94.55	x	x	x	XS	40	
	14.000	355,6	0.469	11.91	67.78	100.94	x	x	x			
	14.000	355.6	0.500	12.70	72.09	107.39	x	x	x			
	14.000	355.6	0.562	14.27	80.66	120.11	x	x	x			
	14.000	355.6	0.594	15.09	85.05	126.71					60	
	14.000	355.6	0.625	15.88	89.28	133.03						
								x	x	x		